

SONIALVISION G4 edition

Multi-purpose Digital R/F System

Better Decisions in Different Examination Environments

Multi-purpose Digital R/F System

SONIALVISION™ G4  edition



With the SONIALVISION G4, Shimadzu offers a multi-functional universal system —one that is useful in a variety of examinations and examination environments, providing optimal image quality, ease of operation, and accommodating patients' comfort.

High Quality Images in Real Time with our without dash


High-resolution and high-contrast images are achieved with real-time image processing.



View both legs, entire chest, or abdomen with a large field of view (up to 17 × 17 inches). Switch to a small field of view for detailed examinations of fingertips or other orthopedic regions.


Advanced digital image processing SCORE PRO Advance

SONIALVISION G4 provides sharp and clear images in various examinations. Especially with fluoroscopy, the background noise component is reduced in real time and the target object is emphasized efficiently. SCORE PRO Advance offers lower exposure levels and optimal image quality.




Adoption of the motion tracking noise reduction

By performing block matching between frames, and recursive processing between the most matched blocks, noise is efficiently reduced without any lag.



Line detected edge enhancement

Emphasizes only the target object without enhancing background noise.




Orthopedic and General Radiography

The large field of view provides the flexibility to accommodate a wide variety of radiographic examinations.




Versatile Design for Various Examinations


The system has been thoughtfully designed to accommodate all users in a diversity of situations, making it ideal for a wide variety of examinations.




Over 2 m Imaging Range



High-quality imaging with minimal halation is possible even with a large field of view.



The X-ray tube can be rotated 90°, allowing for imaging while using a stretcher.




Simple chest imaging is possible by extending the X-ray tube column. **OPTION**

Applications for Supporting Orthopedic Examinations

SLOT Advance **OPTION**


This produces long-view images by focusing X-rays through a slot as the imaging unit is moved parallel to the patient in order to acquire successive images that are automatically stitched together into a single long image.



A series of slot-shaped images is acquired several centimeters apart as the imaging unit (X-ray tube and FPD) is moved.




Slot images are automatically stitched together to create a single long-view image.



Lower dose SLOT Radiography (for lower limbs only)

Based on the thickness of the patient's body, the X-ray conditions are adjusted automatically, ensuring that an optimal amount of X-ray is radiated.


Tomosynthesis **OPTION**



Imaging technology that fuses cone-beam CT reconstruction with digital image processing.

Dual Linear Drive Tomosynthesis

This tomosynthesis radiography method moves the FPD parallel to the X-ray tube focal point. Tomosynthesis can increase the amount of information provided in images by minimizing the truncation area of incident X-rays and reconstructing a larger effective area. The smaller truncation areas also result in less radiation exposure that does not contribute to diagnosis.



T-smart PRO assisted by AI*

Shimadzu's Proprietary Reconstruction Method that Reduces Metal Artifacts


T-smart tomosynthesis includes AI image processing functionality based on deep learning technology. That means tomosynthesis images reconstructed with metal artifacts minimized can be acquired easily by simply pressing the exposure button one time to reduce the time and effort required for examinations.

*The AI (Artificial Intelligence) technology used in T-smart PRO is a "trained model" that was trained at some point and performed accuracy evaluation. It doesn't continue learning after installation.




Gastrointestinal Series and Swallowing Examination (Video fluoroscopy)

17 x 17 inches of large field of view and high image quality are perfect for everything from routine checkups to specialized examinations and observations.



Wheelchair patients can be examined simply by extending the SID.

Fluoroscopic images can be saved in DICOM format.



Smart FOV (Field of View) OPTION

Even if the region of interest is not centered on the monitor, the position of the field of view can be easily adjusted without moving the patient.


*This function is only available at 15 fps or lower.

Urological Examination

Urological imaging with a large field of view while being dose conscious, together with a wealth of additional functions, is provided in support of urological examination.

The edge of the imaging range can be positioned as close as 9.5 cm from the head-end of the table (given a 17-inch FOV), making it easy to perform procedures using an optical endoscope.

Uro Tracking




The table can be tilted relative to any reference position. Examinations can be performed without changing the region of interest height, even if the table is tilted moved without moving the patient.

Uro collimation



Normal collimation



Uro collimation

A specialized collimation function is used for effective dose reduction.

Options for urological examinations OPTION

A full range of urological accessories, such as Leg support and Drain bag, endoscopy support.



Leg support



Disposable drain bag



Voiding cystography chair



Foot controller



Endoscopic Examinations

Achieves both the high image quality and low dose levels necessary for sophisticated interventional procedures.



*The monitor support is not included in the system.
It is purchased item from other manufactures.

The vertical drive unit on the back side of the R/F table is designed to be very compact.
That ensures a high degree of freedom for laying out systems in combination
with a monitor support system.

Achieves High Image Quality
with Low Exposure Levels

SCORE PRO Advance

Noise components are reduced in real time to efficiently
enhance only the target areas being observed. That
enables both intensive exposure reduction and improved
fluoroscopic image quality even for biliopancreatic
endoscopy.



The flat gutter-free table top design provides easy
patient transfer and is easy to clean.
A wide, fully flat table with a high weight capacity
enhances patient safety even during endoscopy
procedures.



Angiography Examinations

Blood vessels can be observed over a large area (Max. 17 x 17 inches).

DA (Serial radiography)

Maximum pulse rate 15 fps

DSA OPTION

Maximum pulse rate 7.5 fps
Remask processing
Reregistration processing
Stacking processing
Land-marking Processing
Road-map fluoroscopy




Movement-tolerant DSA RSM-DSA (Real time Smoothed Mask DSA)


RSM-DSA is a mask-free DSA imaging technique that Shimadzu succeeded in developing first in the market. Misregistration due to respiratory or body movements is less likely to occur, so the patient does not need to hold his or her breath during the test.

That means both DSA images and RSM-DSA images can be
obtained from a single exposure, so that the RSM-DSA mode can
be enabled to continue an examination if the patient moves.


More information can be obtained by comparing images to DSA
images, such as by determining the relative positions of blood
vessels and bones or displaying a scale with images.




Ordinary DSA of Hepatic Artery



RSM-DSA of Hepatic Artery



Ordinary DSA of Shunt



RSM-DSA of Shunt







Functionality for Reducing Radiation Exposure Levels

Various functionalities are included for efficiently reducing exposure levels to provide a low-exposure examination environment for both patients and attending personnel.


To efficiently minimize exposure levels during examinations, the system features grid controlled pulsed fluoroscopy with wave tail elimination. In addition, intelligent BH (Beam-Hardening) filters are automatically selected according to the type of examination, reducing unnecessary X-ray that do not contribute to the actual images.



Exposure Dose Levels Displayed in Real Time

Calculated dose values are displayed on the monitor in real time. In addition to using the display as a guideline for exposure levels during examinations, the dose values can also be managed as examination information via the network.


A dose area product meter can also be installed. OPTION



The removable grid provides a further advantage in dose reduction and is especially important when radiation exposure is of particular concern, such as in pediatrics, urology and gynecology.


Advanced digital image processing

Dose information can be sent to the server via DICOM Storage. OPTION
CSV files can be exported to media.




Solutions for Patient and Healthcare Worker Safety

The user-friendly system is designed to provide a more comfortable examination environment for both patients and medical staff.




Up to:318 kg (700 lb)

The 318 kg (700 lb) weight capacity is ample for even very heavy patients.



The table can be lowered to help older patients easily get on or off the table.



47 cm

With a minimum table height setting of 47 cm, even older patients can get on and off the table with ease.



Soft rubber surrounds the collimator output port to provide cushioning in case the patient is bumped. The clean-look new design covering all the cables around the X-ray tube ensures hygienic advantages.



The console is designed so operations can be performed more comfortably for stress-free examinations.


The compact digital control system is tucked neatly away under the remote control console to provide an uncluttered look without consuming valuable space in the control room.

The dual system enables fully parallel processing for processing images, registering patients, transferring images, or performing other tasks concurrently during examinations.

Fluoroscopy table, X-ray controller, and digital image processing unit operations are always linked to minimize operating steps and ensure examinations can be accomplished easily.


Virtual Collimation

Virtual collimation allows user to collimate the region of interest before X-ray exposure.




Smart FOV (Field of View) OPTION

Smart FOV allows for the adjustment of the field of view's position without X-ray exposure. Dose-less positioning can be achieved using Smart FOV.




*This function is just allowed in under 15 fps rate.

Several types of monitor carts and local consoles are available for your selection to accommodate various examination room layouts and clinical applications. OPTION



Excellent Network compatibility ensures smooth patient registration, image printing, and storage. OPTION



Label Description: X-RAY TV SYSTEM SONIALVISION G4

Founded in 1875, Shimadzu Corporation, a leader in the development of advanced technologies, has a distinguished history of innovation built on the foundation of contributing to society through science and technology. We maintain a global network of sales, service, technical support and applications centers on six continents, and have established long-term relationships with a host of highly trained distributors located in over 100 countries. For information about Shimadzu, and to contact your local office, please visit our website at www.shimadzu.com



Shimadzu Corporation

Headquarters

1, Nishinokyo-Kuwabara-cho, Nakagyo-ku, Kyoto 604-8511, Japan
<https://www.shimadzu.com/med/>



Shimadzu Corporation Medical Systems Division has been certified by TÜV Rheinland as a manufacturer of medical systems in compliance with ISO9001:2015 Quality Management Systems and ISO13485:2016 Medical Devices Quality Management Systems.

Remarks:

- Every value in this catalogue is a standard value, and it may vary a little from the actual at each site.
- The appearances and specifications are subject to change for reasons of improvement without notice.
- Items and components in the photos may include optional items. Please confirm with your sales representative for details.
- System configurations and options may not be available depending on the country. Please confirm with your sales representative for details.
- Before operating this system, you should first thoroughly review the Instruction Manual.
- SONIALVISION G4 is a trademarks of Shimadzu Corporation or its affiliated companies in Japan and/or other countries.
- Company names, products/service names and logos used in this publication are trademarks and trade names of Shimadzu Corporation, its subsidiaries or its affiliates, whether or not they are used with trademark symbol "TM" or "®". Third-party trademarks and trade names may be used in this publication to refer to either the entities or their products/services, whether or not they are used with trademark symbol "TM" or "®". Shimadzu disclaims any proprietary interest in trademarks and trade names other than its own.